



1300

Metal Shield

Product Description

MCM 1300 Metal Shield is a waterborne alkyd formulated for direct-to-metal applications. It has superior hardness and adhesion. It can be applied to most bare metal surfaces and act as a top coat.

Product Features

- Maximum adhesion
- Anti-rust technology
- Long lasting gloss finish
- Easy application
- Food grade certified
- Easy to clean
- Excellent in high-traffic areas
- Mildew resistant
- Available in anti-rust primer
- Available in factory black

Recommended Uses

- Aluminum
- Galvanized
- Steel
- Wood
- Perfect on doors & trim
- Interior or Exterior
- Heavy Equipment
- Metal Structures

Surface Preparation

All surfaces must be clean, sound and dry. Dull gloss surfaces by sanding or applying liquid sander. Fill holes and cracks with appropriate compound. Use #40 surface conditioner before application if chalk is present.

Application

May be applied by brush, roller or spray. Apply generously to achieve maximum coverage.

For any other instruction call MCM Paints 863-9496

Spreading Rate

300-400 sq. ft. per gallon depending on the type of application and the porosity of the surface being painted.

Drying Time

Dries to touch in 30 minutes and can be recoated in 2-3 hours or overnight depending on drying conditions.

Clean Up

Clean hands, tools and equipment promptly with warm soapy water.

Characteristics

Finish: High Gloss

Color: White and can be tinted to any custom color

Generic Type: Styrene Acrylic

Solvent: Water

Weight per Gallon: 10.0 lbs

CAUTION!

KEEP FROM FREEZING

Do not take internally. Close container after each use.

USE WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN

LIMITATION OF LIABILITY

This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**

WARNING! Removal of old paint by sanding, scraping or other means may generate fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of properly fitted protective equipment such as a respirator and proper containment and cleanup. For more information call the national Lead Information Center at 1-800-424-LEAD.