



# 2600

Primaseal Primer/Sealer

## Product Description

MCM #2600 primaseal is a high quality 100% acrylic primer/sealer. It is fast drying and provides an excellent base coat. Can be recoated with alkyd or latex coatings.

## Product Features

- Premium Quality
- Mildew Resistant
- Soap and water clean up
- Excellent adhesion
- Easy to apply
- Low odor
- Rust inhibitive
- Stain block technology
- High Hide
- Satisfaction Guaranteed

## Recommended Uses

- For interior or exterior use
- Bare concrete
- Wood
- Cured Stucco
- Drywall
- Doors
- Block
- Any porous bare surface.

**For fresh stucco use #2614**

## Surface Preparation

All surfaces must be clean, sound and dry. Dull gloss surfaces by sanding or applying liquid sander. Fill holes and cracks with appropriate compound.

## Application

May be applied by brush, roller or spray. Apply generously to prime surface pours.

For any other instruction call  
MCM Paints 863-9496

## Spreading Rate

300-400 sq. ft. per gallon depending on the type of application and the porosity of the surface being painted.

## Drying Time

Dries to touch in 1 hour and can be recoated in 2-3 hours or overnight depending on drying conditions.

## Clean Up

Clean hands, tools and equipment promptly with warm soapy water.

## Characteristics

**Finish:** Flat

**Color:** White and can be tinted to pastel colors

**Generic Type:** Acrylic

**Solvent:** Water

**Weight per Gallon:** 10.7 lbs

**Volume Solids:** 39.2%

**Weight Solids:** 53%

**V.O.C.:** .73lb/gl

### **CAUTION!**

**KEEP FROM FREEZING**

Do not take internally. Close container after each use.

**USE WITH ADEQUATE VENTILATION.**

**KEEP OUT OF REACH OF CHILDREN**

### **LIMITATION OF LIABILITY**

This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**

**WARNING!** Removal of old paint by sanding, scraping or other means may generate fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of properly fitted protective equipment such as a respirator and proper containment and cleanup. For more information call the national Lead Information Center at 1-800-424-LEAD.