



# 2800

Primaseal Alkyd Undercoater

## Product Description

**MCM #2800 Primaseal Alkyd Undercoater** is formulated to seal a variety of surfaces. Has excellent sealing and hold out properties. Brushes freely, levels out well, has high build characteristics and dries quickly. Can be top coated with alkyd or latex coatings.

## Product Features

- Excellent sanding and sealing properties
- High hide
- Bridges hairline cracks
- Blocks stains
- Works over oil-based coatings
- Seals wood and prevents future rotting
- Blocks mildew
- High solids

## Application

May be applied by brush, roller or spray. It is not recommended to reduce. Apply generously and spread evenly to obtain uniformity. Do not apply in direct sunlight. Contact MCM Paints for further questions 863-984-9496

## Recommended Uses

- For interior or exterior use
- Use over existing oil based coatings
- Wood
- Plaster
- Drywall
- Stucco
- Metal

## Surface Preparation

All surfaces must be clean, sound and dry. Dull glossy surfaces. Fill holes and cracks with appropriate compound. Previously painted surfaces require no special priming. Chalky surfaces should be sealed with #40 surface conditioner prior

## Spreading Rate

300-400 square feet per gallon depending on surface condition.

## Drying Time

Dries to touch in 4 hours. May be recoated after 24 hours. Dry times may vary depending on temperature, humidity and air movement.

## Clean Up

Clean hands, tools and equipment promptly with mineral spirits.

## Characteristics

**Finish:** Low Luster  
**Generic Type:** Alkyd  
**Solvent:** Mineral Spirits  
**Weight per Gallon:** 12.6lb  
**Flash Point:** 105 Degrees F  
**V.O.C.** 339 g/l

**CAUTION! COMBUSTIBLE**  
**KEEP OUT OF REACH OF CHILDREN**  
Keep away from heat and flame. Avoid prolonged contact with skin and breathing vapor or spray mist. Do not take internally. Close container after each use.  
**USE ADEQUATE VENTILATION**

**LIMITATION OF LIABILITY**  
This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. **MCM Paints** will replace such quantity of this paint that is proved to be defective. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**

**WARNING!** Removal of old paint by sanding, scraping or other means may generate fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of properly fitted protective equipment such as a respirator and proper containment and cleanup. For more information call the national Lead Information Center at 1-800-424-LEAD.